



Roll Fluting Machines

Models & Specifications

Model No.	Max Turning Diameter	Max Overall Length
K-RFM 302	300 mm	2000 mm
K-RFM 300	300 mm	2500 mm
K-RFM 303	300 mm	3000 mm
K-RFM 352	350 mm	2000 mm
K-RFM 350	350 mm	2500 mm
K-RFM 353	350 mm	3000 mm
K-RFM 452	450 mm	2000 mm
K-RFM 450	450 mm	2500 mm
K-RFM 453	450 mm	3000 mm
K-RFM 652	650 mm	2000 mm
K-RFM 650	650 mm	2500 mm
K-RFM 653	650 mm	3000 mm
K-RFM 852	850 mm	2000 mm
K-RFM 850	850 mm	2500 mm
K-RFM 853	850 mm	3000 mm



Technical Data of Cylindrical Roll Fluting Machine

This fluting machine serves to flute blunt chilled cast iron rolls (mill rolls), but it also fulfills the requirement of other types of industries where chilled rolls are employed for similar purposes. For example: fluting/corrugation of rolls used in flour mills, feed mills, oil seed crushing etc.

Capacity

- Spiral cutting up to 20%. Left and right spiral can be cut.
- Number of flutes up to 1200 on circumference.

Features

- Extra heavy duty cast iron bed forms a rigid base where the machine table travels on Prismatic and Flat guides.
- Main table movement with the roll is hydraulic.
- Fluting head is mounted on machine base.
- Easy positioning of fluting head.
- Complete with fluting tool holder.
- Forward and reverse movement of the fluting tool is hydraulic and linked to the forward and reverse movement main roll table.
- The fluting control is carried out by driving head and indexing gears.
- The roll spiral and indexing is automatically driven by the carriage movement and ratchet mechanism.
- Automatic Forced lubrication system with timer ensures perfect lubrication of all moving parts and guides.
- Rolls support universal type with tail center and steadies.
- Time taken to flute the rolls is reduced to more than 75% due to rapid reverse movement of main table.
- Equipped with all necessary motors and electric panels.

Advantages.

1. Vibration free travel of the table even at the moment of reversal.
2. Variable speeds of forward and reverse motions of table are achievable due to hydraulic controls.
3. Forced Lubrication of all moving parts fitted with automatic timer pump.
4. Ease of operation by the operator control. Accident proof owing to the simple and robust design.
5. Time taken to flute the rolls is reduced to more than 75% due to rapid reverse movement of main table.

The machine will include all necessary motors and electric panels.



KAY JAY
CHILL ROLLS PVT LTD
[HTTP://WWW.KJROLLS.COM](http://www.kjrolls.com)

27, INDUSTRIAL AREA
PHASE - II
PANCHKULA - 134113
INDIA

TEL: +91 172 259 4531
TEL: +91 172 258 1665
FAX: +91 172 256 8156
E-MAIL: SALES@KJROLLS.COM